

Features

- ▶ All-steel 2U durable chassis construction.
- ▶ European and Japanese components ensure optimal result.
- ▶ Short circuit, DC output and peak voltage limit.
- ▶ Power regulated switching power supply.

Technical Specifications

Model - Topology D	LAQ-1004	LAQ-1504
No. Of Channels	2	2
MAX Output Power RMS 1KHz		
2Ω	1300 W	2000 W
4Ω	1000 W	1500 W
8Ω	650 W	875 W
16Ω	400 W	500 W
Bridge 4Ω	2600 W	4000 W
Bridge 8Ω	2000 W	3000 W
Frequency Response Power Bandwidth +/-0.50dB	15Hz-28kHz	
Total Harmonic Distortion 20Hz - 20kHz	0.08%	
Cross Talk 20Hz - 20kHz	≥82dB	
Input Sensitivity @ 8 Ω	0.775V, 1.0V, 32dB	
Signal-to-Noise-Ratio A Weighted	>105	
Protection Circuits	Short Circuit DC Offset & Overheat	
Rack Mount Space	2U	
Dimensions / W x H x D (mm) / W x H x D (inches)	483x 88 x 467 19 x 3.5 x 18.4	
Weight	12Kg	
Net / Shipping	14Kg	